

# Automation 效率高/品質穩定 High Efficiency / Stable Quality

## KA-BH/11-F-3 5 6





■ YouTube



### 輸送帶平台式下擺/袖口折縫

### Conveyor Flat type Bottom/Sleeve Hemming


#### 特點/Feature

- 1. 標準化的車縫品質,排除人工作業的差異。只需人工上料,其餘工序自動完成Standardized sewing quality eliminates differences in manual work. Only manual loading, and the rest of the process is completed automatically.
- 以輸送帶傳送,配備電子式導邊系統,入布精準,效率高
   The transmission is done by conveyor with

electronic hemming guide system, which the fabric loading is accurate and efficient.

- 3. 適用下擺/袖口/口袋等多種的平面式折縫。
  The hemming of bottom/ sleeve/ pocket is applicable.
- 4. 標配自動收料功能,並可選備自動上料系統。 Auto stacking is a standard function. Moreover, auto-material loading system is optional.







型號 Model	KA-BH/ 11-F-□□□
縫紉機機頭 Machine Head	CTD 9311
車縫速度 Sewing Speed	Max. 3500spm
針距規格 Gauge	240, 348, 356, 364
適用布料 Applicable Material	針織布/彈性布 Knits/ Elastic fabric
應用範圍	①下擺寬度: 10~80 cm ②折邊寬度: 1.5~3.5 cm
Application Range	1
產能 Production Capacity	600~900 pcs/hr
電力需求 Power	220V, 1000W
空壓需求 Compressed Air	4 Bar, 240L/min
機器尺寸 Machine Dimension (W x D x H)	230 x 61 x 145 cm
淨重/毛重 Net/ Gross Weight	kg/ kg