

Automation 效率高/品質穩定 High Efficiency / Stable Quality

KA-WB/9304-24





■ YouTube



環型褲腰鬆緊帶車縫

Tubular Elastic Waist Band Attaching

特點/Feature


- 標準化的車縫品質,排除人工作業的差異。只需人工上料,其餘工序自動完成
 Standardized sewing quality eliminates differences in manual work. Only manual loading, and the rest of the process is completed automatically.
- 2. 卓越的糾偏性能,起縫與結束的線跡對齊,誤 差1mm以內


The sewing starting and ending are aligned by the tolerance of 1 mm.

 鬆緊帶褲腰車縫分為前後工段,本機為前工段, 可搭配後工段自動機,效率更高。

Elastic waistband sewing has 2 processes. This model is for the 1^{st} process. It is recommended to work together with the 2^{nd} process automatic machine.









型號 Model	KA-WB/9304-□□
縫紉機機頭 Machine Head	UHD 9304
車縫速度 Sewing Speed	Max. 5000spm
針距規格 Gauge	三線:04, 四線:24
適用布料 Applicable Material	針織布/彈性布 Knits/ Elastic fabric
應用範圍 Application Range	①鬆緊帶寬度: 1.5~4.5 cm ②褲腰週長: 70~180 cm
產能 Production Capacity	150~220 pcs/hr
電力需求 Power	220V, 1000W
空壓需求 Compressed Air	4 Bar, 140L/min
機器尺寸 Machine Dimension (W x D x H)	120 x 76 x 168 cm
淨重/毛重 Net/ Gross Weight	kg/ kg



Automation 效率高/品質穩定 High Efficiency / Stable Quality

KA-WB/9000-3 5 6





YouTube



環型褲腰鬆緊帶壓縫 Talandar Flantia Maiat Pan

Tubular Elastic Waist Band Top Stitch

特點/ Feature

- 標準化的車縫品質,排除人工作業的差異。只需人工上料,其餘工序自動完成
 Standardized sewing quality eliminates differences in manual work. Only manual loading, and the rest of the process is completed automatically.
- 2. 卓越的糾偏性能,起縫與結束的線跡對齊,誤 差1mm以內
 - The sewing starting and ending are aligned by the tolerance of 1 mm.







型號 Model	KA-WB/9000-□□□
縫紉機機頭	CTD 9000
Machine Head	012 3000
車縫速度 Sewing Speed	Max. 3500spm
針距規格 Gauge	356, 364,
適用布料 Applicable Material	針織布/彈性布 Knits/ Elastic fabric
	①褲腰週長: 70~180 cm
應用範圍 Application Range	②鬆緊帶寬度: 1.5~4.5 cm
產能 Production Capacity	150~220 pcs/hr
電力需求 Power	220V, 1000W
空壓需求 Compressed Air	4 Bar, 190L/min
機器尺寸 Machine Dimension (W x D x H)	120 x 76 x 175 cm
淨重/毛重 Net/ Gross Weight	kg/ kg